



**Applications: Computer Rooms / Computer Labs,  
Bank Data Centers, Reservation Centers,  
Networked Offices . See Note Below \*\***

**Compu-tile® / LAN Broadloom**

**LAN 1™ - 4U022 Computile  
Brdlm – 4U030**

construction:

Textured Graphic Loop

fiber:

100% Solution Dyed Nylon  
Recycled Fiber (67%)  
BASF Solution Dyed Nylon (33%)

weight:

Yarn Production Weight-  
Carpet Tile- 24 oz./sq. yd.  
Broadloom- 24 oz./sq. yd.  
Total Weight-  
Carpet Tile- 107 oz./sq. yd.  
Broadloom- 54 oz./sq. yd.

production gauge: 1/10"

backing system:

Carpet Tile- Dissipative EcoWorx  
Broadloom- Dissipative Unitary

**LAN 2.2™ - 4U067**

construction:

Standard- Textured Graphic Loop

fiber:

Solutia LXI Type 6,6 Nylon  
64% yarn dyed/ 33% solution dyed

weight:

Yarn Production Weight-  
Carpet Tile- 26 oz./sq. yd.

Total Weight

Carpet Tile- 107 oz./sq. yd.

production gauge: 1/10"

**NOTE:**

**\*\*Compu-tile is not suitable for use in Mission Critical Areas, such as Air Traffic Operations Areas, 911 Call Centers, or Electronic Mfg including Manufacturing Test, Storage & Lab areas. Julie Industries Staticsmart™ Carpet is recommended for these areas. Call 1-800-225-6052 for addn information**

**Common specifications**

sizes:

Carpet Tile-



24" x 24"

stock: LAN 1, LAN 2.2,

Broadloom-



12'

stock: LAN 1 unitary back only

**advanced static control:**

Conductive Fiber - helix™ 44 Denier  
Conductive Monofilament  
Electrical Resistance- NFPA 99  
1.0 x 10<sup>6</sup> Ohms Minimum  
1.0 x 10<sup>8</sup> Ohms Maximum RTT  
1.0 x 10<sup>9</sup> Ohms Maximum RTG

Groundable Path- 5 mm Copper Strip

backing system:

Carpet Tile- Dissipative EcoWorx

conductive adhesives:

Carpet Tile Releasable Adhesive-  
1.0 x 10<sup>6</sup> Ohms RTT  
Brdloom adhesive Multi-purpose  
use with copper grounding  
strips, 24" x 2".

flammability:

ASTM E-648 Flooring Radiant Panel-  
Class 1 (≥ .45 w/cm<sup>2</sup>)  
ASTM E-662 NBS Smoke Density-  
Less than 450

availability:

Stock Colors and Sizes-  
No minimum  
Non Stock Colors/Sizes-  
750 sq. yd. minimum

Samples available:

1-800-257-7429

